
# Therma-Tru® Light Commercial/Multi-Family - Doors and Frames

## GENERAL NOTES


- Material shown on these drawings will be fabricated only after formal approval by the architect, receipt of approval hardware schedule, and all necessary hardware templates.
- All frames shall be shipped “knocked-down” unless otherwise specified.
- All frames and doors shall be chemically washed, rinsed, and dried prior to receiving one coat of paint.
- Doors and frames will be reinforced for surface mounted hardware as required. Drilling and tapping for surface mounted hardware shall be applied by others.
- It will be the responsibility of the General Contractor to coordinate hardware locations.
- All frames will be supplied with the required wall and floor anchors as illustrated on the frame detail sheet.
- All frames and doors wll be tagged with shop marks. This schedule can be used to cross reference shop marks with architects marks.
- These drawings are not intended for use by other trades.
- Field welding, grinding, finishing, and attachment of field splices by others.

## DOOR HANDING CHART

### SINGLE DOORS




### PAIRS OF DOORS




- All standard type hardware will be located at this manufacturer’s standard locations as shown on the door and frame elevations. Hardware items such as panic exit devices, deadbolts, etc. will also be located at manufacturer’s standard locations unless specifically advised.
- Installations of all glass and glazing to be performed by others.
- Doors, frames, and finished hardware to be installed by others.
- Anchor bolts and expansion shields for any type fastener to be furnished by others.
- All frames must be set absolutely plumb, square, and level.
- All frames will be supplied with rubber door silencers: three for single swing openings and two per header for double swing openings.

| | |
|---|---|
| **JOB NUMBER:** | |
| **PROJECT:** | |
| **LOCATION:** | |
| **ARCHITECT:** | |
| **CONTRACTOR:** | |
| **FINISHED HARDWARE BY:** | |
| **SHEET NUMBER:** | **OF** |

| **RECORD OF SUBMITTALS** | |
|---|---|
| **SUBMITTED** | **RETURNED** |
| **1st** | |
| **2nd** | |
| **3rd** | |
| **4th** | |
| **RECORDED APPROVED DRAWINGS** | |
| **RECORDED APPROVED HARDWARE** | |
| **DRAWN BY:** | |


# Therma-Tru® Light Commercial/Multi-Family - Schedule

| LOCATION | | | | | | FRAME DATA | | | | | | | | | | DOOR DATA | | | | HARDWARE | | | | | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | DOOR OPENING | | | | | | | | | | | | | | | | | |
| ITEM | QUANTITY | ARCH MARK | FROM | TO | SWING | FRAME CONSTR. | GAUGE | WIDTH | HEIGHT | DOOR THICK. | ELEV. / SHEET | SECT. / SHEET | JAMB DEPTH | OVERALL HEIGHT | ANCHOR | DOOR CONSTR. | GAUGE | ELEV. / SHEET | LABEL | HINGE | LOCK | CLOSER | FLUSH BOLTS | HRDWR. SET/ HDG. | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |


JOB NUMBER PROJECT SHEET NUMBER OF LOCATION

# Therma-Tru® Light Commercial/Multi-Family - 22-Gauge & 24-Gauge Steel Doors


## DOOR ELEVATIONS - FLUSH - LITED





EXPOSED GLASS
SIZE: 3" x 33"





EXPOSED GLASS
SIZE: 4" x 25"





EXPOSED GLASS
SIZE: 5" x 20"




EXPOSED GLASS
SIZE: 10" x 10"





EXPOSED GLASS
SIZE: 22" x 28"





EXPOSED GLASS
SIZE: 22" x 34"


## DOOR ELEVATIONS - EMBOSSED - OPAQUE




STYLE# SE210HD




STYLE# 514




STYLE# SE960HD



STYLE# SE969HD




STYLE# SE978HD




STYLE# 500

# Therma-Tru® Light Commercial/Multi-Family - FG Doors


## DOOR ELEVATIONS - SMOOTH




STYLE# SSF100



STYLE# SSF160




STYLE# SSF200




STYLE# SSF960


## DOOR ELEVATIONS - GRAINED



STYLE# FCF100




STYLE# FCF140




STYLE# FCF160

# Therma-Tru® Light Commercial/Multi-Family - Standard Hardware Preps.


## 4" x 4" HINGE DETAIL





## STANDARD LATCH PREP




## LATCH PREPS





STANDARD 1 1/18" x 2 1/4" STRIKE WITH OPTIONAL 1 1/18" x 2 1/4"DEADBOLT PREP.





1 1/4" x 8" MORTISE LOCK PREP. NOTE: MORTISE LOCK IS NOT OFFERED WITH LANDMARK DOORS.

## STEEL DEADBOLT PREP




STAMPED 1 1/18" x 2 3/4" OPTIONAL DEADBOLT PREP FOR STEEL FRAMES. AVAILABLE WITH ADJUSTA-FIT, ADJUSTA-TRIM, & SECURA-FIT FRAMES.

## STEEL TEE STRIKE PREP




STAMPED TEE STRIKE PREP FOR STEEL FRAMES. AVAILABLE WITH ADJUSTA-FIT, ADJUSTA-TRIM & SECURA-FIT FRAMES.

## STEEL LIP STRIKE PREP



STAMPED LIP STRIKE PREP FOR STEEL FRAMES. AVAILABLE WITH ADJUSTA-FIT, ADJUSTA-TRIM & SECURA-FIT FRAMES.


## STEEL 4 7/8" ANSI PREP



STAMPED 4 7/8" ANSI STRIKE PREP FOR STEEL FRAMES. AVAILABLE WITH ADJUSTA-FIT, ADJUSTA-TRIM & SECURA-FIT FRAMES.

# Therma-Tru® Light Commercial/Multi-Family - Hardware Locations

## STANDARD STEEL ENTRANCE DOORS





NOTES:

HINGE BACKSET = 5/32"

22 GA. = .027 MIN.
24 GA. = .023 MIN

DOORS UNDER 6-8 OR OVER 7-0 ARE AVAILABLE. CONTACT YOUR REP. FOR MORE INFO.

## HARDWARE LOCATIONS




UNDERCUT OPTIONS:

STANDARD - 1 3/4"

PUBLIC ACCESS - 1 1/8"

NO SILL OPTION - 3/4"

***STANDARD 1 3/4" DOOR, HINGE and CYLINDER LOCK LOCATIONS:***

***DOOR WIDTH***

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **NOMINAL** | 2-0 | 2-4 | 2-6 | 2-8 | 2-10 | 3-0 | 3-6 |
| **ACTUAL** | 23 11/16" | 27 11/16" | 29 11/16" | 31 11/16" | 33 11/16" | 35 11/16" | 41 11/16" |

***DOOR HEIGHT***


| **NOMINAL** | 6-8 | 7-0 | 8-0 |
|---|---|---|---|
| **ACTUAL** | 78 5/8" | 82 1/8" | 93" |
| **MORTISE PREP** | 45 1/4" | 45 1/4" | 59 5/8" |
| **CYLINDRICAL PREP** | 44 7/8" | 44 7/8" | 59 1/4" |

| | |
|---|---|
| **JOB NUMBER** | |
| **PROJECT** | |
| **LOCATION** | |
| **SHEET NUMBER** | **OF** |


| | |
|---|---|
| JOB NUMBER | |
| PROJECT | |
| LOCATION | |
| SHEET NUMBER | OF |

# Therma-Tru® Light Commercial/Multi-Family - Adjusta-Fit® Frames - Single


## HARDWARE LOCATIONS





## FRAME DETAIL




## AVAILABLE THRESHOLDS





## ADJUSTA-FIT KERFED FRAME




| NOMINAL FRAME OPENING | | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT - STD | ROUGH OPENING HEIGHT - BARRIER FREE | ROUGH OPENING HEIGHT - NO SILL OPTION |
|---|---|---|---|---|---|
| | 2-0 x 6-8 | 25" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 2-4 x 6-8 | 29" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 2-6 x 6-8 | 31" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 2-8 x 6-8 | 33" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 2-10 x 6-8 | 35" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 3-0 x 6-8 | 37" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 3-6 x 6-8 | 43" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 2-0 x 7-0 | 25" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 2-4 x 7-0 | 29" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 2-6 x 7-0 | 31" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 2-8 x 7-0 | 33" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 2-10 x 7-0 | 35" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 3-0 x 7-0 | 37" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 3-6 x 7-0 | 43" | 84 1/4" | 83 5/8" | 83 1/4" |

| WALL SIZE | CLOSURE MODEL |
|---|---|
| 3 3/8" - 3 3/4" | 3 |
| 3 3/4" - 4 1/8" | 3A |
| 4 1/8" - 4 5/8" | 4 |
| 4 5/8" - 5" | 4A |
| 5 1/8" - 5 5/8" | 5 |
| 5 5/8" - 6" | 5A |
| 6 1/8" - 6 5/8" | 6 |
| 6 5/8" - 7" | 6A |
| 7 1/8" - 7 5/8" | 7 |
| 7 5/8" - 8" | 7A |
| 8 1/8" 8 5/8" | 8 |
| 8 5/8" - 9" | 8A |
| 9 1/8" - 9 5/8" | 9 |
| 9 5/8" - 10" | 9A |
| 10 1/8" - 10 5/8" | 10 |

## ADJUSTA-FIT FRAMES





| | |
|---|---|
| **THRESHOLDS** | |
| | TWO PIECE |
| | BARRIER FREE |
| **HINGES** | |
| | REMOVABLE PIN |
| | NON-REMOVABLE PIN |
| | SPRING LOADED |
| | BALL BEARING |
| **LATCH PREPS** | |
| | 4 7/8" ANSI (STD) |
| | T-STRIKE w/ DEADBOLT |


# Therma-Tru® Light Commercial/Multi-Family - Adjusta-Fit® Frames - Double

## HARDWARE LOCATIONS


**NOTE:** BASE FRAME = 16-GA.
CLOSURE FRAME = 22-GA.





## FRAME DETAIL




## AVAILABLE THRESHOLDS





## ADJUSTA-FIT KERFED FRAME




| WALL SIZE | CLOSURE MODEL |
|---|---|
| 3 3/8" - 3 3/4" | 3 |
| 3 3/4" - 4 1/8" | 3A |
| 4 1/8" - 4 5/8" | 4 |
| 4 5/8" - 5" | 4A |
| 5 1/8" - 5 5/8" | 5 |
| 5 5/8" - 6" | 5A |
| 6 1/8" - 6 5/8" | 6 |
| 6 5/8" - 7" | 6A |
| 7 1/8" - 7 5/8" | 7 |
| 7 5/8" - 8" | 7A |
| 8 1/8" 8 5/8" | 8 |
| 8 5/8" - 9" | 8A |
| 9 1/8" - 9 5/8" | 9 |
| 9 5/8" - 10" | 9A |
| 10 1/8" - 10 5/8" | 10 |

| NOMINAL FRAME OPENING | | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT - STD | ROUGH OPENING HEIGHT - BARRIER FREE | ROUGH OPENING HEIGHT - NO SILL OPTION |
|---|---|---|---|---|---|
| | 4-0 x 6-8 | 49 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 5-0 x 6-8 | 61 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 5-4 x 6-8 | 65 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 6-0 x 6-8 | 73 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 4-0 x 7-0 | 49 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 5-0 x 7-0 | 61 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 5-4 x 7-0 | 65 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 6-0 x 7-0 | 73 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |


## ADJUSTA-FIT FRAMES





| THRESHOLDS | |
|---|---|
| | TWO PIECE |
| | BARRIER FREE |
| **HINGES** | |
| | REMOVABLE PIN |
| | NON-REMOVABLE PIN |
| | SPRING LOADED |
| | BALL BEARING |
| **LATCH PREPS** | |
| | 4 7/8" ANSI (STD) |
| | T-STRIKE w/ DEADBOLT |

# Therma-Tru® Light Commercial/Multi-Family - Adjusta-Trim® Frames - Single


## HARDWARE LOCATIONS





## FRAME DETAIL




## AVAILABLE THRESHOLDS





## ADJUSTA-TRIM KERFED FRAME




| NOMINAL FRAME OPENING | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT - STD | ROUGH OPENING HEIGHT - BARRIER FREE | ROUGH OPENING HEIGHT - NO SILL OPTION |
|---|---|---|---|---|
| 2-0 x 6-8 | 25" | 80 3/4" | 80 1/8" | 79 3/4" |
| 2-4 x 6-8 | 29" | 80 3/4" | 80 1/8" | 79 3/4" |
| 2-6 x 6-8 | 31" | 80 3/4" | 80 1/8" | 79 3/4" |
| 2-8 x 6-8 | 33" | 80 3/4" | 80 1/8" | 79 3/4" |
| 2-10 x 6-8 | 35" | 80 3/4" | 80 1/8" | 79 3/4" |
| 3-0 x 6-8 | 37" | 80 3/4" | 80 1/8" | 79 3/4" |
| 3-6 x 6-8 | 43" | 80 3/4" | 80 1/8" | 79 3/4" |
| 2-0 x 7-0 | 25" | 84 1/4" | 83 5/8" | 83 1/4" |
| 2-4 x 7-0 | 29" | 84 1/4" | 83 5/8" | 83 1/4" |
| 2-6 x 7-0 | 31" | 84 1/4" | 83 5/8" | 83 1/4" |
| 2-8 x 7-0 | 33" | 84 1/4" | 83 5/8" | 83 1/4" |
| 2-10 x 7-0 | 35" | 84 1/4" | 83 5/8" | 83 1/4" |
| 3-0 x 7-0 | 37" | 84 1/4" | 83 5/8" | 83 1/4" |
| 3-6 x 7-0 | 43" | 84 1/4" | 83 5/8" | 83 1/4" |

| WALL SIZE | CLOSURE MODEL |
|---|---|
| 4 1/8" - 4 5/8" | 4 |
| 4 5/8" - 5" | 4A |
| 5 1/8" - 5 5/8" | 5 |
| 5 5/8" - 6" | 5A |
| 6 1/8" - 6 5/8" | 6 |
| 6 5/8" - 7" | 6A |
| 7 1/8" - 7 5/8" | 7 |
| 7 5/8" - 8" | 7A |
| 8 1/8" 8 5/8" | 8 |
| 8 5/8" - 9" | 8A |
| 9 1/8" - 9 5/8" | 9 |
| 9 5/8" - 10" | 9A |
| 10 1/8" - 10 5/8" | 10 |


## ADJUSTA-TRIM FRAMES





| THRESHOLDS | | WEATHERSTRIPPING | | STRIKE PREPS | | HINGES | | FIRE RATINGS | |
|---|---|---|---|---|---|---|---|---|---|
| Two-Piece | X | | | Lip Strike w/ Opt. Deadbolt | X | Removable Pin | X | "B" Rating 1 1/2 Hour | X |
| Barrier Free | X | Compression | X | T-Strike w/ Opt. Deadbolt | X | Non-Removable Pin | X | "C" Rating 3/4 Hour | |
| Frost Break Inswing: FBI | | | | 4 7/8" ANSI w/ Opt. Deadbolt | X | Ball Bearing | X | No Rating | |
| Frost Break Outswing: FBO | | | | 4 7/8" ANSI w/ Multi-Deadbolt | X | Spring Loaded | X | | |

# Therma-Tru® Light Commercial/Multi-Family - Adjusta-Trim® Frames - Double


## HARDWARE LOCATIONS





## FRAME DETAIL




## AVAILABLE THRESHOLDS





## ADJUSTA-TRIM KERFED FRAME




| NOMINAL FRAME OPENING | | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT - STD | ROUGH OPENING HEIGHT - BARRIER FREE | ROUGH OPENING HEIGHT - NO SILL OPTION |
|---|---|---|---|---|---|
| | 4-0 x 6-8 | 49 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 5-0 x 6-8 | 61 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 5-4 x 6-8 | 65 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 6-0 x 6-8 | 73 1/2" | 80 3/4" | 80 1/8" | 79 3/4" |
| | 4-0 x 7-0 | 49 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 5-0 x 7-0 | 61 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 5-4 x 7-0 | 65 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |
| | 6-0 x 7-0 | 73 1/2" | 84 1/4" | 83 5/8" | 83 1/4" |

| WALL SIZE | CLOSURE MODEL |
|---|---|
| 4 1/8" - 4 5/8" | 4 |
| 4 5/8" - 5" | 4A |
| 5 1/8" - 5 5/8" | 5 |
| 5 5/8" - 6" | 5A |
| 6 1/8" - 6 5/8" | 6 |
| 6 5/8" - 7" | 6A |
| 7 1/8" - 7 5/8" | 7 |
| 7 5/8" - 8" | 7A |
| 8 1/8" 8 5/8" | 8 |
| 8 5/8" - 9" | 8A |
| 9 1/8" - 9 5/8" | 9 |
| 9 5/8" - 10" | 9A |
| 10 1/8" - 10 5/8" | 10 |


## ADJUSTA-TRIM FRAMES





| THRESHOLDS | | WEATHERSTRIPPING | | STRIKE PREPS | | HINGES | | FIRE RATINGS | |
|---|---|---|---|---|---|---|---|---|---|
| Two-Piece | X | | | Lip Strike w/ Opt. Deadbolt | X | Removable Pin | X | "B" Rating 1 1/2 Hour | X |
| Barrier Free | X | Compression | X | T-Strike w/ Opt. Deadbolt | X | Non-Removable Pin | X | "C" Rating 3/4 Hour | |
| Frost Break Inswing: FBI | | | | 4 7/8" ANSI w/ Opt. Deadbolt | X | Ball Bearing | X | No Rating | |
| Frost Break Outswing: FBO | | | | 4 7/8" ANSI w/ Multi-Deadbolt | X | Spring Loaded | X | | |

# Therma-Tru® Light Commercial/Multi-Family - Secura-Fit® Frames - Single


## HARDWARE LOCATIONS




## FRAME DETAIL




## AVAILABLE THRESHOLDS





| NOMINAL FRAME OPENING | | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT |
|---|---|---|---|
| | 2-0 x 6-8 | 24" - 24 1/4" | 79 7/8" - 80 1/4" |
| | 2-4 x 6-8 | 28" - 28 1/4" | 79 7/8" - 80 1/4" |
| | 2-6 x 6-8 | 30" - 30 1/4" | 79 7/8" - 80 1/4" |
| | 2-8 x 6-8 | 32" - 32 1/4" | 79 7/8" - 80 1/4" |
| | 2-10 x 6-8 | 34" - 34 1/4" | 79 7/8" - 80 1/4" |
| | 3-0 x 6-8 | 36" - 36 1/4" | 79 7/8" - 80 1/4" |
| | 2-0 x 7-0 | 24" - 24 1/4" | 83 7/8" - 84" |
| | 2-4 x 7-0 | 28" - 28 1/4" | 83 7/8" - 84" |
| | 2-6 x 7-0 | 30" - 30 1/4" | 83 7/8" - 84" |
| | 2-8 x 7-0 | 32" - 32 1/4" | 83 7/8" - 84" |
| | 2-10 x 7-0 | 34" - 34 1/4" | 83 7/8" - 84" |
| | 3-0 x 7-0 | 36" - 36 1/4" | 83 7/8" - 84" |

| THRESHOLDS | |
|---|---|
| | TWO PIECE |
| | BARRIER FREE |
| **HINGES** | |
| | REMOVABLE PIN |
| | NON-REMOVABLE PIN |
| | SPRING LOADED |
| | BALL BEARING |
| **LATCH PREPS** | |
| | T-STRIKE (STD) |
| | T-STRIKE w/ DEADBOLT |
| | 4 7/8" ANSI |
| | 4 7/8" ANSI w/ DEADBOLT |


| | |
|---|---|
| JOB NUMBER | |
| PROJECT | |
| LOCATION | |
| SHEET NUMBER | OF |

# Therma-Tru® Light Commercial/Multi-Family - Secura-Fit® Frames - Double


## HARDWARE LOCATIONS




## FRAME DETAIL




## AVAILABLE THRESHOLDS




| NOMINAL FRAME OPENING | | ROUGH OPENING WIDTH | ROUGH OPENING HEIGHT |
|---|---|---|---|
| | 4-0 x 6-8 | 47 3/4" - 48" | 79 7/8" - 80 1/4" |
| | 5-0 x 6-8 | 59 3/4" - 60" | 79 7/8" - 80 1/4" |
| | 5-4 x 6-8 | 63 3/4" - 64" | 79 7/8" - 80 1/4" |
| | 6-0 x 6-8 | 71 3/4" - 72" | 79 7/8" - 80 1/4" |
| | 4-0 x 7-0 | 47 3/4" - 48" | 83 7/8" - 84" |
| | 5-0 x 7-0 | 59 3/4" - 60" | 83 7/8" - 84" |
| | 5-0 x 7-0 | 63 3/4" - 64" | 83 7/8" - 84" |
| | 6-0 x 7-0 | 71 3/4" - 72" | 83 7/8" - 84" |

| THRESHOLDS | |
|---|---|
| | TWO PIECE |
| | BARRIER FREE |
| **HINGES** | |
| | REMOVABLE PIN |
| | NON-REMOVABLE PIN |
| | SPRING LOADED |
| | BALL BEARING |
| **LATCH PREPS** | |
| | T-STRIKE (STD) |
| | T-STRIKE w/ DEADBOLT |
| | 4 7/8" ANSI |
| | 4 7/8" ANSI w/ DEADBOLT |

| | |
|---|---|
| JOB NUMBER | |
| PROJECT | |
| LOCATION | |
| SHEET NUMBER | OF |